



NOMINAL AIRFLOW (l/s)		ECM (W)	FULL LOAD AMPS		SOUND (dBA)		UNIT WEIGHT (kg)
MIN	MAX		230 V		142 l/s	260 l/s	
70	283	246	2.3		46	59	57

STANDARD CONSTRUCTION:

- WHITE POWDER COAT FINISH, 1000 HR SALT SPRAY RATED
- FAN ON/OFF SWITCH
- EXTERNAL FAN ADJUSTMENT
- CASTERS SHIP LOOSE
- ASSEMBLY LISTED UNDER UL507/CSA 22.2 No.113 & UL867/CSA 22.2 No.187
- BIPOLAR IONISER MEETS UL 2998

NON STANDARD CONSTRUCTION:

- 1.2 mm GAUGE CONSTRUCTION
- VARIABLE SPEED EC MOTOR, 50 HZ
- CUSTOMER PROVIDED POWER CORD

OPTIONS:

- UV LIGHT
- BIPOLAR IONISATION
- BIPOLAR IONISATION & UV LIGHT



PROJECT:		HOLYOAKE AIR MANAGEMENT SOLUTIONS by PRICE	
ENGINEER:		KR	RAP ROOM AIR PURIFIER 283 l/s HEPA RECIRCULATION UNIT
CUSTOMER:			
SUBMITTAL DATE:	SPEC. SYMBOL:	2023/09/14	